

Service Manual



HRM-6



HRM-5

ORDER NO.
RRV4652

PROFESSIONAL REFERENCE MONITOR HEADPHONES

HRM-6 /XEGWL

HRM-5 /XEGWL

1. SPECIFICATIONS

HRM-6

Type Fully enclosed dynamic headphones
Impedance 45 Ω
Sensitivity 102 dB
Frequency response 5 Hz to 40 000 Hz
Maximum input power 2 000 mW
Driver units ϕ 40 mm dome type
Plug ϕ 3.5 mm stereo mini-plug
(gold plated, threaded type)
HEad cushion Polyurethane (leather finish)
Ear pad Polyurethane (leather finish)
Weight 265 g (without cord)
Accessories ϕ 6.3 mm standard stereo plug adapter
(gold plated, threaded type),
Carrying pouch,
1.2 m long one-side connection coiled type
(extended length 3.0 m),
3.0 m straight cable, 1.2 m straight cable

NOTE:

Specifications and design are subject to possible
modifications without notice due to improvements.

HRM-5

Type Fully enclosed dynamic headphones
Impedance 32 Ω
Sensitivity 100 dB
Frequency response 5 Hz to 30 000 Hz
Maximum input power 1 700 mW
Driver units ϕ 40 mm dome type
Plug ϕ 3.5 mm stereo mini-plug
(gold plated, threaded type)
HEad cushion Polyurethane (leather finish)
Ear pad Polyurethane (leather finish)
Weight 260 g (without cord)
Accessories ϕ 6.3 mm standard stereo plug adapter
(gold plated, threaded type),
Carrying pouch,
1.2 m long one-side connection coiled type
(extended length 3.0 m),
3.0 m straight cable

NOTE:

Specifications and design are subject to possible
modifications without notice due to improvements.

About the label of production lot

2.1 EXPLODED VIEWS



12.00P6-2001

EXPLODED VIEWS Parts List

Q.No.	Description	Part No.	Mark No.	Description	Part No.
1	EAR PAD (HRM-6)	26.00P6-2800	5	HEADBAND ASSY (HRM-6)	12.00P6-2001
1	EAR PAD (HRM-5)	26.00P5-2800	5	HEADBAND ASSY (HRM-5)	12.00P5-2002
2	SP BASE ASSY L (HRM-6)	12.00P6-A000	6	SCREW	33.2035-2101
2	SP BASE ASSY L (HRM-5)	12.00P5-A000	7	SCREW	33.2060-2100
3	SP BASE ASSY R (HRM-6)	12.00P6-A001			
3	SP BASE ASSY R (HRM-5)	12.00P5-A001			

* There is no need for the measuring instrument or line