


Pioneer

Service Manual



X-CM31-K

ORDER NO.
RRV4350

CD RECEIVER SYSTEM

X-CM31-K

/SYXE8

X-CM31-W,-R,-T

/SYXE8

X-CM31-K,-W

/CXE

X-CM31DAB-K,-W,-R,-T

/VXE8

THIS MANUAL IS APPLICABLE TO THE FOLLOWING MODEL(S) AND TYPE(S).

Model	Type	Power Requirement	Remarks
X-CM31-K	SYXE8	AC 220 V to 240 V	
X-CM31-W	SYXE8	AC 220 V to 240 V	
X-CM31-R	SYXE8	AC 220 V to 240 V	
X-CM31-T	SYXE8	AC 220 V to 240 V	
X-CM31-K	CXE	AC 120 V	
X-CM31-W	CXE	AC 120V	
X-CM31DAB-K	VXE8	AC 220 V to 240 V	
X-CM31DAB-W	VXE8	AC 220 V to 240 V	
X-CM31DAB-R	VXE8	AC 220 V to 240 V	
X-CM31DAB-T	VXE8	AC 220 V to 240 V	



PIONEER CORPORATION 1-1, Shin-ogura, Saiwai-ku, Kawasaki-shi, Kanagawa 212-0031, Japan
PIONEER ELECTRONICS (USA) INC. P.O. Box 1760, Long Beach, CA 90801-1760, U.S.A.
PIONEER EUROPE NV Haven 1087, Keetberglaan 1, 9120 Melsele, Belgium
PIONEER ELECTRONICS ASIACENTRE PTE. LTD. 253 Alexandra Road, #04-01, Singapore 159936
©PIONEER CORPORATION 2012

K-FZV AUG. 2012 Printed in Japan

9.2 EXTERIOR SECTION

ABE205240-0001

*1 :  Glues
Silicon Bond (GYA 001) application position

