


Service Manual



VSX-AX5i-S

ORDER NO.
RRV2801

AUDIO/VIDEO MULTI-CHANNEL RECEIVER

VSX-AX5i-S

VSX-AX3-S

VSX-AX3-K

THIS MANUAL IS APPLICABLE TO THE FOLLOWING MODEL(S) AND TYPE(S).

Model	Type	Power Requirement	The voltage can be converted by the following method.
VSX-AX5i-S	HYXJI	AC220-230V	AC240V, *
VSX-AX3-S	HYXJI	AC220-230V	AC240V, *
VSX-AX3-K	HYXJI	AC220-230V	AC240V, *

*: Alter the wiring of the power-supply block at the primary winding of Power transformer referring to the Line Voltage Selection described in Service Manual.



For details, refer to "Important symbols for good services".

PIONEER CORPORATION 4-1, Meguro 1-chome, Meguro-ku, Tokyo 153-8654, Japan
PIONEER ELECTRONICS (USA) INC. P.O. Box 1760, Long Beach, CA 90801-1760, U.S.A.
PIONEER EUROPE NV Haven 1087, Keetberglaan 1, 9120 Melsele, Belgium
PIONEER ELECTRONICS ASIACENTRE PTE. LTD. 253 Alexandra Road, #04-01, Singapore 159936
©PIONEER CORPORATION 2003

T-ZZE JULY 2003 printed in Japan

